PRODUCT FICHE

Product sheet prepared in accordance with the Commission Delegated Regulation (EU) No 65/2014

Supplier name		C D A
	Model	CCH60BL
Supplier's model identifier	Туре	CCH60BL
	Index	1193913
Annual energy consumption (AEC _{hood}) [KWh / year]		52,7
Energy efficiency class		А
Fluid dynamic efficiency (FDE _{hood})		29.5
Fluid dynamic efficiency class		А
Lighting efficiency (LE _{hood}) [lux/W]		40
Lighting efficiency class		A
Grease filtering efficiency (GFE _{hood})		57
Grease filtering efficiency class		E
Air flow rate (at min / max speed) [m³/h]		245 / 415
Air flow rate (at high speed/turbo mode) [m³/h]		665
Noise level at min / max speed [dB]		49 / 62
Noise level at min / max speed (at high speed/turbo mode) [dB]		69
Power consumption in the off-mode P _o [W]		0
Power consumption in standby mo	ode P _s [W]	0,45
Power consumption in standby mo	ode P _s [W]	0,

To determine the results, and in accordance with the requirements in relation to the labelling of energy-related products and with regard to ecodesign requirements, the following calculation and measurement methods were applied:

- Directive of the European Parliament and of the Council 2010/30/EU: REGULATION NO 65/2014.
- Directive of the European Parliament and of the Council
- Directive of the European Parliament and of the Council 2009/125/EC; REGULATION NO 66/2014, EN 50564 Electrical and electronic household and office equipment. Measurement of low power consumption EN 60704-2-13 Household and similar electrical appliances.
- Test code for the determination of airborne acoustical noise. Particular requirements for range hoods
- EN 61591 Household range hoods and other cooking fume extractors – Methods for measuring performance

SPECIFICATION

INFORMATION ON DOMESTIC RANGE HOODS

0 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	CCH60BL
Supplier's model identifier	1193913
Time increase factor (f)	0.9
Energy Efficiency Index (EEI _{hood})	53.7
The air flow rate measured at the best efficiency point (Q _{BEP}) [m³/h]	341,1
Air pressure measured at the best efficiency point (P_{BEP}) [Pa]	445
The maximum air flow rate (Q _{max}) [m³/h]	665
Power consumption measured at the best efficiency point $(W_{\rm BEP})$ [W]	142,8
Nominal power of the lighting system [W _L] [W]	8
Average illumination of the lighting system on the cooking surface (E _{middle}) [lux]	320
Sound power level (L _{WA}) [dB]	62
Minimum distance between cooker hood and the hob's surface [mm]	650
Voltage [V/Hz]	AC 220-240V / 50-60Hz
Incandescent / halogen / LED light	LED strip
Total power consumption [W]	276
Protection class	1
Eco-Boost [min]	5
Width [mm] x Depth [mm] x Height [mm]	589 x 290 x 320 - 320
Outlet [mm]	150
Appliance weight [kg]	10

Information relevant to users in order to reduce the overall impact of the cooking process on the environment

In order to reduce the overall impact of cooking process on the environment.

- when cooking in pots and pans always cover them with lids, remember to turn off the hood at the end of cooking (or use countdown timer – available on some models),
- remember to turn off hood lighting at the end of cooking,
 use appropriate cooking zone and adjust the flame to the size of
- the pot.
- only use the highest hood fan speed at high fume concentration in the kitchen
- regularly clean/replace filters (clean filters improve the hood efficiency).