



EVX140SS Ceiling extractor

Features

- Ducted/re-circulating installation
- · Soft touch buttons
- 3 speeds + intensive
- Boost function
- Clean air function
- Timer: 30 minute timer
- Type of grease filter: Stainless steel grease filters
- Filter saturation warning light
- Remote control
- Lighting: 4 x 35W halogen lights
- Peripheral aspiration
- Motor included

Available in

Stainless steel

Energy

• Energy rating: D

Filters

- Number of charcoal filters (optional): 2
- Charcoal filter code: CHA18
- Ducting kit: AED61/63/64

Lighting

- Number of lights: 0
- Type of light: 4x35W halogen

Extraction rates and noise

- Noise level: 0dBA
- Extraction rate at first speed: 319m³/hr
- Noise level at first speed: 52dBA
- Extraction rate at second speed: 530m³/hr
- Noise level at second speed: 63dBA
- Extraction rate at third speed: 680m³/hr
- Noise level at third speed: 68dBA
- Extraction rate at fourth speed: 770m³/hr
- Noise level at fourth speed: 70dBA

Technical specification

- Max storage time (power failure): 1800hours
- Rated electrical power: 415
- Required height over gas hobs: 750mm (min)
- Required height over electric hobs: 750mm (min)
- Motor Input: 275W
- Power supply: 3A
- El-202
- Protection class: I
- Outlet diameter: 150mm
- Optional accessories: Ducting kit aed61/63/64

Fitting notes

- Recommended ceiling height 1500-1800mm
- The EVX140SS extraction outlet can be rotated through 90° 180° or 270° allowing for flevible installatic

