



3U10SS Updraft extractor

Features

- Ducted/re-circulating installation
- Touch control
- 3 speeds + intensive
- Timer: 10 minute timer
- Aluminium grease filter
- Filter saturation warning light
- 1 x 10W LED strip light

Available in

- Stainless steel with black glass fascia

Energy

- C

Filters

- Aluminium grease filter
- Number of grease filters: 1
- Number of charcoal filters (optional): 1
- Ducting kit: AED61/63/64
- CHA32

Lighting


- 1x10W strip light

Extraction Rates And Noise

- Extraction rate at first speed: 228m³/hr
- Noise level at first speed: 52dBA
- Extraction rate at second speed: 332m³/hr
- Noise level at second speed: 53dBA
- 496
- Noise level: 68dBA
- Extraction rate at third speed: 430m³/hr
- Noise level at third speed: 61dBA
- Extraction rate at fourth speed: 496m³/hr
- Noise level at fourth speed: 68dBA

Technical Specification

- Required height over gas hobs: 650mm (min)
- Required height over electric hobs: 650mm (min)
- Power supply: 3A
- Pressure value: 450Pa
- Outlet diameter: 150mm
- Outlet diameter: 150mm
- Optional accessories: Chimney section, AEC02SS
- Motor Input: 8
- 90



Line drawing includes the optional chimney accessory (code: AEC02SS)