



**ECN62BL Flat glass extractor**

**Features**

- Ducted/re-circulating installation
- 3 speeds
- Aluminium grease filter
- Push button control

**Available in**

- Stainless steel
- Black

**Energy**

- D

**Filters**

- Charcoal filters: CHA12 (pack of 1)
- Number of layers: 4
- Number of grease filters: 1
- Number of charcoal filters (optional): 1
- Ducting kit: AED61/63/64 or AED51/53/54 with adaptor

**Extraction Rates And Noise**

- Extraction rate at first speed: 218m<sup>3</sup>/hr
- Noise level at first speed: 50dBA
- Extraction rate at second speed: 302m<sup>3</sup>/hr
- Noise level at second speed: 58dBA
- 391
- Noise level: 60dBA
- Extraction rate at third speed: 391m<sup>3</sup>/hr
- Noise level at third speed: 60dBA

**Technical Specification**

- Required height over gas hobs: 700mm (min)
- Required height over electric hobs: 600mm (min)
- Power supply: 3A
- Mains lead length: 1m
- Mains lead rating: H05VV-F
- Class I
- Outlet diameter: 120mm/150mm
- Outlet diameter: It is best to use the AED6 (150mm) ducting kit rather than the AED5 (120mm) with the adaptor. This keeps noise levels to a min
- 104

**Fitting Notes**

- Please ensure is sufficient to between the h

