



## ECN92SS Flat glass extractor

### Features

- Ducted/re-circulating installation
- 3 speeds
- Aluminium grease filter
- 2 x 2W LED lights
- Push button control

### Available in

- Stainless steel

### Energy

- D

### Filters

- Charcoal filters: CHA12 (pack of 1)
- Number of layers: 4
- Number of grease filters: 1
- Number of charcoal filters (optional): 1
- Ducting kit: AED61/63/64 or AED51/53/54 with adaptor
- CHA12

### Lighting

- LED
- Number of lights: 2

### Extraction Rates And Noise

- Extraction rate at first speed: 218m<sup>3</sup>/hr
- Noise level at first speed: 50dBA
- Extraction rate at second speed: 302m<sup>3</sup>/hr
- Noise level at second speed: 58dBA
- 391
- Noise level: 60dBA
- Extraction rate at third speed: 391m<sup>3</sup>/hr
- Noise level at third speed: 60dBA

### Technical Specification

- Required height over gas hobs: 700mm (min)
- Required height over electric hobs: 600mm (min)
- Power supply: 3A
- Mains lead length: 1m
- Mains lead rating: H05VV-F
- Class I
- Outlet diameter: 120mm/150mm
- Outlet diameter: It is best to use the AED6 (150mm) ducting kit rather than the AED5 (120mm) with the adaptor. This keeps noise levels to a min
- Motor Input: 1
- 104

### Fitting Notes

- Please ensure is sufficient to between the h

