



# ECPK90SS Curved glass island extractor

#### Features

- Ducted/re-circulating installation
- Push button control
- 3 speeds
- Type of grease filter: Aluminium grease filters

#### Available in

Stainless steel

## Energy

• Energy rating: D

#### Filters

- Number of layers: 4
- Number of grease filters: 2
- Number of charcoal filters (optional): 2
- Charcoal filter code: CHA25
- Ducting kit: AED61/63/64 or AED51/53/54 with adaptor

#### Extraction rates and noise

- Extraction rate: 387
- Noise level: 61dBA
- Extraction rate at first speed: 224m<sup>3</sup>/hr
- Noise level at first speed: 50dBA
- Extraction rate at second speed: 322m3/hr
- Noise level at second speed: 56dBA
  Extraction rate at third speed: 387m<sup>3</sup>/hr
- Noise level at third speed: 61dBA

### **Technical specification**

- Required height over gas hobs: 700mm (min)
- Required height over electric hobs: 600mm (min)
- Power supply: 3A
- Mains lead length: 1m
- H05VV-F
- Class I
- Outlet diameter: 120mm/150mm
- Outlet diameter: It is best to use the AED6 (150mm) ducting kit rather than the AED5 (120mm) with the adaptor. This keeps noise levels to a minimum.

#### Fitting notes

 Please ensure that you check the ceiling height is sufficient to allow the required clearance between the behand extractor.

