



## ECPK90SS Curved glass island extractor

### Features

- Ducted/re-circulating installation
- Push button control
- 3 speeds
- Type of grease filter: Aluminium grease filters

### Available in

- Stainless steel

### Energy

- Energy rating: D

### Filters

- Number of layers: 4
- Number of grease filters: 2
- Number of charcoal filters (optional): 2
- Charcoal filter code: CHA25
- Ducting kit: AED61/63/64 or AED51/53/54 with adaptor

### Extraction rates and noise

- Extraction rate: 387
- Noise level: 61dBA
- Extraction rate at first speed: 224m<sup>3</sup>/hr
- Noise level at first speed: 50dBA
- Extraction rate at second speed: 322m<sup>3</sup>/hr
- Noise level at second speed: 56dBA
- Extraction rate at third speed: 387m<sup>3</sup>/hr
- Noise level at third speed: 61dBA

### Technical specification

- Required height over gas hobs: 700mm (min)
- Required height over electric hobs: 600mm (min)
- Power supply: 3A
- Mains lead length: 1m
- H05VV-F
- Class I
- Outlet diameter: 120mm/150mm
- Outlet diameter: It is best to use the AED6 (150mm) ducting kit rather than the AED5 (120mm) with the adaptor. This keeps noise levels to a minimum.

### Fitting notes

- Please ensure that you check the ceiling height is sufficient to allow the required clearance between the hob and extractor.

