



## EVC4SS Cylinder extractor

### Features

- Ducted/re-circulating installation
- Soft touch buttons
- 3 speeds + intensive
- Clean air function
- Timer: 15 minute timer
- Aluminium grease filter
- Filter saturation warning light
- Peripheral aspiration
- 2 x 20W halogen lights

### Available in

- Stainless steel
- Black

### Energy

- D

### Filters

- Number of grease filters: 1
- Number of charcoal filters (optional): 2
- Ducting kit: AED61/63/64
- CHA2

### Extraction Rates And Noise

- Extraction rate at first speed: 225m<sup>3</sup>/hr
- Noise level at first speed: 43dBA
- Extraction rate at second speed: 332m<sup>3</sup>/hr
- Noise level at second speed: 54dBA
- Extraction rate at third speed: 452m<sup>3</sup>/hr
- Noise level at third speed: 60dBA
- Extraction rate at fourth speed: 501m<sup>3</sup>/hr
- Noise level at fourth speed: 62dBA

### Technical Specification

- Required height over gas hobs: 650mm (min)
- Required height over electric hobs: 650mm (min)
- Power supply: 3A
- Pressure value: 436Pa
- Outlet diameter: 150mm
- Motor Input: 250W
- 290

### Fitting Notes

- Please ensure that you check the ceiling height is sufficient to between the h

