



EVCK4BL Cylinder island extractor

Features

- Ducted/re-circulating installation
- Soft touch buttons
- 3 speeds + intensive
- Clean air function
- Timer: 15 minute timer
- Type of grease filter: Aluminium grease filter
- Filter saturation warning light
- Peripheral aspiration
- Speeds:
- 2 x 20W halogen lights

Available in

- Black
- Stainless steel

Energy

- Energy rating: D

Filters

- Number of grease filters: 1
- Number of charcoal filters (optional): 2
- Charcoal filter code: CHA2
- Ducting kit: AED61/63/64

Lighting

- Halogen
- 20W
- Number of lights: 2

Extraction Rates And Noise

- Extraction rate:
- Extraction rate at first speed: 225m³/hr
- Noise level at first speed: 43dBA
- Extraction rate at second speed: 332m³/hr
- Noise level at second speed: 54dBA
- Extraction rate at third speed: 452m³/hr
- Noise level at third speed: 60dBA
- Extraction rate at fourth speed: 501m³/hr
- Noise level at fourth speed: 62dBA

Technical Specification

- Required height over gas hobs: 650mm (min)
- Required height over electric hobs: 650mm (min)
- Power supply: 3A
- Pressure value: 436Pa
- Outlet diameter: 150mm
- 290
- Motor Input: 250W

