



EVCK4SS Cylinder island extractor

Features

- Door open alarm: 2
- Reversible door: 400
- Exterior colour of cabinet: 2
- Interior colour of cabinet: 20
- Display adjustable C/F: 436
- Ducted/re-circulating installation
- Soft touch buttons
- 3 speeds + intensive
- Clean air function
- Timer: 15 minute timer
- Type of grease filter: Aluminium grease filter
- Filter saturation warning light
- Peripheral aspiration

Available in

- Black
- Stainless steel

Energy

- Energy rating: D

Filters

- Number of grease filters: 1
- Number of charcoal filters (optional): 2
- Charcoal filter code: CHA2
- Ducting kit: AED61/63/64

Extraction rates and noise

- Noise level: 0dBA
- Extraction rate at first speed: 225m³/hr
- Noise level at first speed: 43dBA
- Extraction rate at second speed: 332m³/hr
- Noise level at second speed: 54dBA
- Extraction rate at third speed: 452m³/hr
- Noise level at third speed: 60dBA
- Extraction rate at fourth speed: 501m³/hr
- Noise level at fourth speed: 62dBA

Technical specification

- Required height over gas hobs: 650mm (min)
- Required height over electric hobs: 650mm (min)
- Power supply: 3A
- Pressure value: 436Pa
- Outlet diameter: 150mm

