



# EVX100SS Ceiling extractor

#### **Features**

- Ducted/re-circulating installation
- · Soft touch buttons
- Boost function
- Clean air function
- Timer: 30 minute timer
- Type of grease filter: Aluminium grease filters
- Filter saturation warning light
- Remote control
- Peripheral aspiration
- Motor included
- 3 + intensive speeds
- Dishwashable grease filter

#### Energy

· Energy rating: D

### Filters

- Number of charcoal filters (optional): 2
- Charcoal filter code: CHA18
- Ducting kit: AED61/63/64

#### Lighting

- Number of lights: 0
- Type of light: 4x 35W halogen lights

#### Extraction rates and noise

- Noise level: 0dBA
- Extraction rate at first speed: 319m<sup>3</sup>/hr
- Noise level at first speed: 52dBA
- Extraction rate at second speed: 530m<sup>3</sup>/hr
- Noise level at second speed: 63dBA
- Extraction rate at third speed: 680m<sup>3</sup>/hr
- Noise level at third speed: 68dBA
- Extraction rate at fourth speed: 770m<sup>3</sup>/hr
- Noise level at fourth speed: 70dBA

## Technical specification

- Max storage time (power failure): 1800hours
- Required height over gas hobs: 750mm (min)
- Required height over electric hobs: 750mm (min)
- Motor Input: 275W
- Power supply: 3A
- El-202
- · Protection class: I
- Optional accessories: Ducting kit aed61/63/64

### Fitting notes

- Recommended ceiling height 1500-1800mm
- The EVX100SS extraction outlet can be rotated through 90°, 180° or 270°, allowing for flexible installation.

